5	-	-		
14			-	
	X	-		
	- 8	: : :		
1				

Product info

In the ITP data group centres, the IT and electricity distribution spaces are located on top of each other. The side of the centre has a cable chute by the IT space for the wiring of the electricity distribution section. This makes it easy to connect a feed cable from the bottom. The IT space can be equipped with a wide variety of fittings, which enable several different uses. Available for both surface and flush mounting. The surface-mounted model contains the necessary feed-through flanges and a fixed back plate. When flush-mounted, the centre only rises 4mm above the wall surface!



Technical details

Electrical number	3312424	Breaker 1-pole B16	-
Ue (V)	230/400	Breaker 1-pole C16	12
In (A)	25	Breaker 1-pole C20	-
IP	20C	Breaker 3-pole C16	-
fn			-
Icw	<5kA		-
Material	Ku-Si	Reserved (mod)	9
Main switch (A)	40	RJ -connector	12x(17*18) +
Breaker 1-pole C6	-		14x(15*19,5)
Breaker 1-pole B10	-	Installation	Uppo tai pinta
Breaker 1-pole C10	9	Väri	RAL9010

E-Contacts: asiakaspalvelu@pok.fi etunimi.sukunimi@pok.fi www.pok.fi Phone numbers: Vaihde: 010 5727 501 Myynti: 010 5727 520 Suunnittelu: 010 5727 530 VAT: 0306687-3 FI03066873

